



KWADLUX QM 2 m




QM201



QM202

KWADLUX		 P[W]	 φ [lm]	
QM.201.24.C.	ST S3 S5 A3 A6	24	1800	3100
QM.201.24.N.		24	2300	4200
QM.201.36.C.		36	2700	3100
QM.201.36.N.		36	3450	4200
QM.202.24.C.	ST S3 S5 A3 A6	2 x 24	3600	3100
QM.202.24.N.		2 x 24	4600	4200
QM.202.36.C.		2 x 36	5400	3100
QM.202.36.N.		2 x 36	6900	4200
Przykład: KWADLUX QM.202.24.N.A3				
MONTAŻ				
KOTWA Q200.14 INOX				







KWADLUX QM 2,5 m




QM251




QM252

KWADLUX				
QM.251.24.C.	ST S3 S5 A3 A6	24	1800	3100
QM.251.24.N.		24	2300	4200
QM.251.36.C.		36	2700	3100
QM.251.36.N.		36	3450	4200
QM.252.24.C.	ST S3 S5 A3 A6	2 x 24	3600	3100
QM.252.24.N.		2 x 24	4600	4200
QM.252.36.C.		2 x 36	5400	3100
QM.252.36.N.		2 x 36	6900	4200
Przykład: KWADLUX QM.252.24.N.A3				
MONTAŻ				
FUNDAMENT LXF1020				



KWADLUX QG






Montaż w podłożu na zewnątrz i wewnątrz obiektów.

Rodzaj profilu	QE5	QE10	QE15
Ilość uchwytów	2	3	4

Opcje:

- nietypowe długości całkowite oprawy,
- wykonanie przelotowe opraw,
- barwy światła: zielona, żółta, czerwona, niebieska,
- inna konstrukcja uchwytów montażowych.



KWADLUX	 P[W]	 Φ [lm]	
QG.5.S.C	2,1	125	3000
QG.5.M.C	3,6	360	2700
QG.5.S.Z	2,1	140	6000
QG.5.M.N	4,8	390	4200
QG.10.S.C	4,2	250	3000
QG.10.M.C	7,2	720	2700
QG.10.S.Z	4,2	280	6000
QG.10.M.N	7,2	780	4200
QG.15.S.C	6,3	375	3000
QG.15.M.C	10,8	1080	2700
QG.15.S.Z	6,3	420	6000
QG.15.M.N	14,4	1170	4200